



## Explore API Documentation

# SelfService\_Compliance\_ActivityTypeText

Version 1.1

Last Modified: 11/14/2023

Last Modified By: Litzy Mora



## Change Log

This changelog only contains significant or notable changes to the revision. Any editorial type changes or minor changes are not included.

Revision	Change Date	Description	Modified By
1.0	06/21/2021	Initial draft	Jackson Bukata
1.1	8/10/2022	Updated data refresh time	Estefany Puc Nieto
1.2	12/20/2022	Updated pagination	Litzy Mora

## Contents

Change Log.....	2
Overview.....	3
Relationships and Dependencies.....	3
API Detail.....	3
Supported Filters.....	3
Fields.....	4
Field Descriptions.....	4
Sample.....	5

## Overview

The Activity Type Text API is designed to expose translated template data from Compliance. **When using this API, please filter by Language ID or Language code to eliminate duplicates.**

## Relationships and Dependencies

From: Table	To: Table	Relationship	Cardinality <sup>1</sup>	Comment
SelfService_Compliance_ActivityTypeText (ATT)	SelfService_Compliance_EventTaskData (ETD)	ATT.InspectActivityTypeId=ETD.InspectActivityTypeId	M:1	



## API Detail

Direction	From Project Suite	
Pagination	5,000 Rows	
Frequency	All Reporting APIs are used by calling a GET method at an interval determined by the customer. InEight suggests using these APIs on an infrequent basis (once per day) to avoid potential performance impact to live systems when the returned data set could be large.	
Trigger Method(s)	All default OData filters are supported	
Average Payload Size	Depends on date range selected	
APIM Name	SelfService_Compliance_ActivityTypeText	
Data Refresh/Delta/Incremental Loads	The data in this API will refresh in five minutes or less from the time it is entered.	
Project Suite	Starting Version	V1.0
	Ending Version	V1.0

## Supported Filters

All default OData filters are supported by this API.

<sup>1</sup> 1:M = One to Many, 1:1 = One to One, M:1 = Many to one

## Fields

Name	Type	CharMaxLength	NumericPrecision	DatePrecision	Product	PK
<b>InspectActivityTypeTextId</b>	Bigint	Null	19	Null	Compliance	X
<b>InspectActivityTypeId</b>	Bigint	Null	19	Null	Compliance	
<b>ActivityTypeName</b>	Nvarchar	250	Null	Null	Compliance	
<b>ActivityTypeDescription</b>	Nvarchar	4000	Null	Null	Compliance	
<b>LanguageId</b>	Bigint	Null	19	Null	Compliance	
<b>LanguageCode</b>	Nvarchar	25	Null	Null	Compliance	
<b>CreatedById</b>	Bigint	Null	Null	Null	Compliance	
<b>CreatedDateChar</b>	Varchar	35	Null	Null	Compliance	
<b>ModifiedById</b>	Bigint	Null	19	Null	Compliance	
<b>ModifiedDateChar</b>	Varchar	35	Null	Null	Compliance	
<b>IsActive</b>	Bit	Null	Null	Null	Compliance	

## Field Descriptions

Name	Description	Example
<b>InspectActivityTypeTextId</b>	Unique identifier assigned to each record in the API	1
<b>InspectActivityTypeId</b>	Id assigned to a template	Safety
<b>ActivityTypeName</b>	Text name of the template name	A module to track and manage safety related business processes
<b>ActivityTypeDescription</b>	Text description of the template	True
<b>LanguageId</b>	Unique value indicating the language Id associated to the record	1
<b>LanguageCode</b>	Code indicating the language Id	en
<b>CreatedById</b>	Unique identifier associated to the creator of the record	14
<b>CreatedDateChar</b>	Indicates the date created	2021-03-17 21:56:29.000000+00:00
<b>ModifiedById</b>	Indicates the Id of individual that made modification	14
<b>ModifiedDateChar</b>	Date of the modification of the record	2021-03-17 21:56:29.000000+00:00
<b>IsActive</b>	Indicates if a record is active or inactive	1

## Sample

```
{"InspectActivityTypeTextId":1,"InspectActivityTypeId":1,"ActivityTypeName":"Test: Pre-Pour Checklist", "ActivityTypeDescription":"Test: Pre-Pour Checklist", "LanguageId":1, "LanguageCode":"en", "CreatedById":60, "CreatedDateChar":"2019-09-16 16:18:07.540276 +00:00", "ModifiedById":60, "ModifiedDateChar":"2019-09-16 16:18:07.540276 +00:00", "IsActive":true}
```